

1. Rack adapters

We offer rack adapters for the installation of all bench mount modls into 19" systems. They are available for mounting heights from 2U to 9U and both for 19" and for ½ 19" units. For retrofitting of 19" rack adapters please state the height oft he front panel!

1.1 Rack adapter for 19" unit



Detail top view

1.2 Rack adapter for ½ 19" unit with ½ 19" blind panel



1.3 Rack adapter for two ½ 19" units



ACCESSORIES:

High voltage cables

TYPE		DESIGN (Diameter in mm)	MAX. CABLE OPERATING VOLTAGE	MATING CONNECTOR (Operating voltage connector)
RG 58	Mat.- Nr.: 502030100			
Capacitance/m:	101pF			
Impedance:	50Ω			
Ambient temperature:	-50°C ... +80°C			
Bending radius:	10cm (repeated) 2,5cm (once)			
Max. current:	max. 10A		10kV DC	SHV 6,5kV
130660	Mat.- Nr.: 0502030130			
Capacitance/m:	82,7pF			
Impedance:	20Ω			
Ambient temperature:	-5°C ... +85°C			
Bending radius:	20cm (repeated) 3cm (once)			
Max. current:	max. 4A		30kV DC	HS21 F3415 20kV
RG 11	Mat.- Nr.: 0502030200			
Capacitance/m:	68pF			
Impedance:	75Ω			
Ambient temperature:	-50°C ... +80°C			
Bending radius:	20cm (repeated) 5 m (once)			
Max. current:	max. 6A		50kV DC	F3430 35kV
C 2124	Mat.- Nr.: 0502032124			
Capacitance/m:	99pF			
Impedance:	61Ω			
Ambient temperature:	-50°C ... +60°C			
Bending radius:	15,2cm			
Max. current:	max. 27A		100kV DC	HVS 65 65kV HVS 100 100kV
C 2121	Mat.- Nr.: 0502032121			
Capacitance/m:	95pF			
Impedance:	51Ω			
Ambient temperature:	-50°C ... +60°C			
Bending radius:	21,6cm			
Max. current:	max. 30A		150kV DC	Special plug, available only complete with cable
C2134	Mat.- Nr.: 0502032134			
Capacitance/m:	102pF			
Impedance:	64W			
Ambient temperature:	-50°C ... +60°C			
Bending radius:	25,4cm			
Max. current:	max. 55A		200kV DC	Special plug, available only complete with cable